



Natural impact noise reducing underlay of coconut fibre

- Only 4 mm thick
- Moisture, rot and mildew resistant
- High levelling capacity
- Environmentally friendly
- Easy to install

CocoFloor® is an impact sound reducing subfloor which also has excellent insulating properties. For example, the thermal resistance (the degree to which the CocoFloor® is resistance to warmth) is 0,12 m² .K/W.

CocoFloor® is delivered on a roll and is easy and simple to lay (A polythene sheet should be used under this product as a moisture barrier). Despite its small thickness of 4 mm, CocoFloor® has a high levelling capacity and is able to absorb small irregularities. CocoFloor® is an environmentally

friendly product, made of coconut fibres in combination with polyester cotton. CocoFloor® is used as an underlay under other Unifloor subfloors or underlayment systems.

The combination of CocoFloor® with Jumpax® Nature and 11 mm engineered wood is a 22 dB solution. In addition, the combination of Redupanel® and CocoFloor® provides a 22 dB solution with 6 and 9 mm solid plank flooring.



PRODUCT SPECIFICATIONS

COCOFLOOR® 4 mm

BY UNIFLOOR

TECHNICAL DATA

Article number	116.000
Thickness/tolerance (mm)	4 / ± 0,6
Size (cm)	1500 x 100
Raw material(s) combinations	Coconut fibre/Polyester Cotton
Colour	Natural
Weight per m ² (kg)	0,650
Weight per roll (kg)	9,75
Density (kg/m ³)	180
Fire class (according to EN13501: 2007)	
Nude test	F _{fl-s1}
Thermal resistance R value (m ² .K/W) (according to ISO 8302:1991 and EN 12667:2001)	0.116
TOG	1.2
Impact sound reduction on concrete floor (according to ISO 10140-3 2010) in combination with REDU-PANEL® and 6 and 9 mm solid plank flooring	22 dB ΔL _w
in combination with Jumpax® Nature and 11 mm engineered wood	22 dB ΔL _w
Impact sound reduction on wooden floor (according to ISO 10140-3 2010 base from 64 dB) in combination with Twinpanel® Base	15 dB ΔL _n
Formaldehyde degree	E-1

APPLICATION

Natural impact sound reducing underlay made of coconut fibre.



ROLL

15 m²

• Width 100 cm

Thickness 4 mm

PACKAGING

Installation instructions present

Packaging	1 box (6 roll) / 90 m ²
Pallet size (l x w x h)	1200 x 800 x 1230 mm
Pallet weight	75 kg



Scan the QR code
for more info
about Cocofloor®
4 mm!

Visit www.unifloor-underlay.com for
the most up-to-date information.

unifloor
UNDERLAY SYSTEMS

Unifloor B.V.
Arnsbergstraat 4
NL - 7418 EZ Deventer

Tel. +31 (0) 570 - 85 55 33
E-mail info@unifloor.nl
www.unifloor.nl



@2022 Unifloor B.V. All rights reserved.